

DIRECT THERMAL LABEL PRINTER

DCCode[®]

DC 421D

- USB + LAN Standard
- Fast print speed 152mm/s or 6 IPS
- Supporting TSPL, EPL, ZPL, DPL Commands
- Optional: Bluetooth, Wi-Fi



Bluetooth



203 DPI

Technical Specifications

Resolution	203DPI
Print method	Direct Thermal
Print speed	152 mm (6") / s
Max.print width	108mm (4.09")
Max.print length	1778mm (70")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4-115mm (1.0"-4.6")
Media thickness	0.06~0.254 mm (2.36~10mil)
Media core diameter	25.4 ~ 76.2 mm (1" ~ 3")
Label length	10 ~ 1778 mm(0.39" ~ 70")
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory upto Max.4GB
Interface	USB + LAN
Processor	32 Bit CPU
1D Barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN, etc.
2D Barcode	PDF-417,Maxicode,DataMatrix, QRcode, Aztec
Internal Fonts	8 alpha-numeric bitmap fonts, Windows fonts can be downloaded
Sensors	Gap sensor & Moveable Black mark sensor
Emulation	TSPL ZPL, EPL, DPL
Dimension	217 mm (D) x 178 mm (W) x 158 mm (H)
Weight	1.2 kg
Print Head Life	25KM
Driver	Windows / Linux / Mac
SDK	Windows / iOS / Android
Input	AC 110-240V,1.8A, 50-60Hz
Output	DC 24V, 2.5A, 60W
Optionals	Bluetooth, Wi-Fi, External Stand
Operational Temp	5° ~ 40°C(41~104°F)Humidity: 25 ~ 85% non-condensing



DCCode[®]

hello@dcodeinternational.in



www.dcodeinternational.in

DELHI NCR

MUMBAI

AHEMDABAD

SURAT

TIRUPUR

CHENNAI

LUDHIANA

PUNE

KOLKATA

COIMBATORE

GUWAHATI

